

TECHNICAL SPECIFICATIONS

Model : SR322-6NP



ITEM	DESCRIPTION
Form	2U standard rack mounted
CPU	Supports 2 Intel 3rd generation Xeon ICE Lake scalable full series processors, Socket-P+ 4189 pin package, TDP 270W
Chipset	Xeon E5-2600V4 (Changeable)
Memory	32 DIMMs, support 2400/2666/2933/3200 DDR4 ECC RDIMM/LRDIMM server memory, support up to 4TB memory, support up to 16 Optane persistent memory 200 series
Controller	Integrated 6Gb/s SATA controller; Optional support for 12Gb/s SAS HBA and 12Gb/s SAS RAID controller
Storage	Front storage: 12 hot-swappable 3.5/2.5" SAS/SATA3.0 hard drives Rear storage: up to 6 hot-swappable 2.5" hard drive bays (optional)
PCIe Slots	Support 5 x standard PCIe expansion slots (5 x PCIe 5.0 x16)
Network	Supports multiple network expansion capabilities. <ul style="list-style-type: none"> ● Onboard network card ● Supports one OCP 3.0 ● Flexible IO card
I/O Ports	USB: 2 USB3.0 on the front (mounting ears), 2 USB3.0 on the rear (onboard) VGA: 1 VGA on the front (mounting ear), 1 VGA on the rear (onboard) COM 1 rear COM interface (onboard)
Management	<ul style="list-style-type: none"> ● Support UEFI ● Support BMC ● Support NC SI ● Support integration by third-party management systems
Security	<ul style="list-style-type: none"> ● Support administrator password ● Support TPM
Dimensions	Rack mounted 2U, width 447x height 87x depth 827mm
Operating Environment	Working temperature 10°C ~ 35°C (without direct light)
Operating Humidity	Working humidity 30% ~ 80% (non-condensing)
Operating Systems	Microsoft Windows Server 、 Microsoft Hyper-V Server 、 Red Hat Enterprise Linux 、 SUSE Linux Enterprise Server 、 CentOS 、 Ubuntu 、 Oracle Linux 、 VMware ESXi 、 Citrix XenServer mainstream operating systems Please consult sales personnel for specific versions